CADILLAC (SGM) ATS-L ATS-L 2.0T (169 KW) T25 (2014 AND AFTER)



ENGINE LTG Ecotec Capacity: 6 liter (Service fill)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Xedoz FE 5W-30	
Change every 7500 km/ 12 months	
USE	CLIMATE
First change only	Moderate
PRODUCT RECOMMENDATION 1	
Xedoz FE 5W-30	
Change every 5000 km/ 12 months	

DIFFERENTIAL REAR			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1011	Syngear TDL 75W-90		

DIFFERENTIAL REAR LIMITED SLIP		
USE	CLIM	MATE
Normal	Mo	derate
PRODUCT RECOMMENDATION 1		
SP Gear LS 1015		

TRANSMISSION AUTOMATIC Hydra-Ma Capacity: 10,5 liter	atic 6L45 6/1
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	
Change every 80000 km	

CADILLAC (SGM) ATS-L ATS-L 2.0T (169 **KW) T25** (2014 AND AFTER)



HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Change over 20000 km/24 months	-	-

Change every 30000 km/24 months

COOLING SYSTEM Capacity: 8,5 liter			
USE		CLIMATE	
Flexible (on board maintenance	e system)	Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15	Coolant SP 15+		
Change every 240000 km/ 60 mont	ths		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.