

**CHERY BONUS BONUS 1.5 (2008-2019)****ENGINE SQR477F**

Capacity: 3,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Emperol 10W-40***Change every 15000 km*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

**Specialsynth MSP 5W-40**

PRODUCT RECOMMENDATION 2

**Emperol 5W-40**

PRODUCT RECOMMENDATION 3

**Asyntho 5W-30***Change every 15000 km*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**Emperol 10W-40***Change every 5000 km*

USE	CLIMATE
Initial service	Cold

PRODUCT RECOMMENDATION 1

**Specialsynth MSP 5W-40**

PRODUCT RECOMMENDATION 2

**Emperol 5W-40**

PRODUCT RECOMMENDATION 3

**Asyntho 5W-30***Change every 5000 km***TRANSAXLE MANUAL 5/1**

Capacity: 2,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Gear 1011**

PRODUCT RECOMMENDATION 2

**Syngear TDL 75W-90**

PRODUCT RECOMMENDATION 3

**Syngear 75W-90***Change every 30000 km/ 12 months***HYDRAULIC BRAKE/CLUTCH SYSTEM**

Capacity: 1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4***Change every 50000 km/ 24 months*

**CHERY BONUS BONUS 1.5 (2008-2019)****POWER STEERING**

Capacity: 0,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Matic 2032</b>	<b>ATF Almirol</b>	

Check every 15000 km

**COOLING SYSTEM**

Capacity: 7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

Check every 15000 km

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*