## CHERY OVE / ALVE OVE / ALVE 1.6 (88 KW) (2008-2015)



ENGINE SQR481F Capacity: 4,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Emperol 10W-40			
Change every 15000 km			
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1			
Emperol 10W-40			
Change every 5000 km			

TRANSAXLE MANUAL QR519Mi Capacity: 2,1 liter	HE 5/1	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90
Change every 30000 km/ 12 month	18	'

HYDRAULIC BRAKE/CLUTCH SYST Capacity: 0-0 liter (Between min and m			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
Change every 50000 km/ 24 months	·		

POWER STEERING Capacity: 0-0 liter (Between min and max.)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Matic 2032	ATF Almirol		
Check every 15000 km			

## CHERY OVE / ALVE OVE / ALVE 1.6 (88 KW) (2008-2015)



COOLING SYSTEM Capacity: 7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Change every 40000 km/24 months	;	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.