

# CHEVROLET (SGM) SAIL SAIL 1.6 8V (2005-2007)

**ENGINE L01**

Capacity: 3,5 liter, Filter capacity: 0,25 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**Asyntho 5W-30***Change every 15000 km/ 12 months*

| USE    | CLIMATE |
|--------|---------|
| Normal | Arctic  |

## PRODUCT RECOMMENDATION 1

**Helar 0W-40***Change every 15000 km/ 12 months***TRANSAXLE AUTOMATIC 4/1**

Capacity: 6 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**SP Matic 2032**

## PRODUCT RECOMMENDATION 2

**ATF Almirol***Change every 90000 km***TRANSAXLE MANUAL 5/1**

Capacity: 1,6 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**SP Gear 5015***Change every 90000 km***HYDRAULIC BRAKE/CLUTCH SYSTEM**

Capacity: 0,45 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

## PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

## PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4***Change every 30000 km/ 24 months*

**CHEVROLET (SGM) SAIL SAIL 1.6 8V (2005-2007)****POWER STEERING**

Capacity: 0,9 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>SP Matic 2032</b>     | <b>ATF Almirol</b>       |          |

Change every 30000 km/ 24 months

**COOLING SYSTEM**

Capacity: 5,8 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant SP 15</b>     | <b>Coolant SP 15+</b>    |          |

Change every 240000 km/ 60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.