NISSAN (DONGFENG) SYLPHY (XUAN YI) SYLPHY (XUAN YI) 2.0 (2006-2011)



ENGINE MR20DE Capacity: 3,8 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 15W-40		
Change every 5000 km/ 6 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza LSP 5W-30	Asyntho 5W-30	Emperol 10W-40

Change every 5000 km/6 months

Check every 40000 km/24 months

TRANSAXLE CVT 1/1 Capacity: 3,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4016	
Check every 15000 km/ 12 months	'

HYDRAULIC BRAKE/CLUTCH SYSTEM				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			

POWER STEERING Capacity: 0,9 liter		
use Normal		climate Moderate
SP Matic 2032	ATF Almirol	ATF Dexron II-D
Check every 10000 km/ 6 months		1

KROON-OIL B.V. Postbus 149 7600 AC Almelo

NISSAN (DONGFENG) SYLPHY (XUAN YI) SYLPHY (XUAN YI) 2.0 (2006-2011)



COOLING SYSTEM Capacity: 7,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Change every 80000 km/ 48 months	·	·

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.