HAIMA (FAW) 7 7 2.0 TP (2012 AND AFTER)



ENGINE HM484Q Capacity: 3,3 liter, Filter capacity: 0,3 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Asyntho 5W-30			
Change every 5000 km/ 6 months			
USE		CLIMATE	
First change only		Moderate	
PRODUCT RECOMMENDATION 1			
Asyntho 5W-30			
Change every 2500 km/ 2 months			

TRANSAXLE MANUAL 5/1 Capacity: 2,1 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Gearlube GL-5 80W-90	
Change every 20000 km/ 24 month	S	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90
Change every 20000 km/ 24 month	S	
USE		CLIMATE
First change only		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Gearlube GL-5 80W-90	
Change every 7500 km/ 6 months		
USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90
Change every 7500 km/ 6 months	· · ·	

HAIMA (FAW) 7 7 2.0 TP (2012 AND AFTER)



HYDRAULIC BRAKE/CLUTCH SYSTEM					
USE		CLIMATE			
Normal		Moderate			
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2				
Drauliquid-S DOT 4	Drauliquid DOT 3				
Check every 5000 km/ 6 months, change e	every 20000 km/ 24 months				
USE		CLIMATE			
Severe		Moderate			
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2				
Drauliquid-S DOT 4	Drauliquid DOT 3				

Change every 12 months

POWER STEERING			
USE	CI	LIMATE	
Normal	N	loderate	
PRODUCT RECOMMENDATION 1			
ATF Dexron II-D			
Check every 5000 km/ 6 months, change every 20000 km/ 24 months			

COOLING SYSTEM Capacity: 6,2-6,8 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
Check every 10000 km/ 10 months, change every 24 months			

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.