HAIMA (FAW) FREEMA FREEMA 1.6 MT HMC6445/HMC6446/HMC7186/HMC7166



(2009 AND AFTER)

ENGINE HM479Q-A Capacity: 3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Asyntho 5W-30	
Change every 5000 km/ 6 months	

TRANSAXLE MANUAL 5/1 Capacity: 2,85 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90
Change every 20000 km/24 month		·

HYDRAULIC BRAKE/CLUTCH SY Capacity: 0,55 liter	'STEM		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-S DOT 4	Drauliquid DOT 3		
Change aven 20000 km/24 month	,		

Change every 20000 km/24 months

POWER STEERING Capacity: 0,8-1,2 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Matic 2032	ATF Dexron II-D		
Check every 5000 km/ 6 months			

Capacity: 3,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 12 EVO	

Change every 10000 km/12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is PRODUCT RECOMMENDATION

HAIMA (FAW) FREEMA FREEMA 1.6 MT HMC6445/HMC6446/HMC7186/HMC7166



(2009 AND AFTER)

advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.