

HAIMA (FAW) M3 M3 1.5 CVT HMA7150-DA4W/-DB4W/-DC4W (2014 AND AFTER)



ENGINE HMA GN15-VF
Capacity: 3,6-3,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30

Change every 5000 km/ 6 months

TRANSAXLE CVT
Capacity: 4,35-6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4016

Check every 10000 km/ 12 months, change every 60000 km

HYDRAULIC BRAKE/CLUTCH SYSTEM
Capacity: 0,57 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

Change every 20000 km/ 24 months

POWER STEERING
Capacity: 1,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

PRODUCT RECOMMENDATION 2

ATF Almirol

Check every 5000 km/ 6 months

COOLING SYSTEM
Capacity: 4,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 12 EVO

Check every 10000 km/ 10 months, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is

PRODUCT RECOMMENDATION

HAIMA (FAW) M3 M3 1.5 CVT HMA7150-DA4W/-DB4W/-DC4W (2014 AND AFTER)



advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.