

# HAIMA (FAW) M5 M5 1.5T AT 6F24 (2014 AND AFTER)



**ENGINE** HMA GN15-TF  
Capacity: 4,6-5,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Asyntho 5W-30**

*Change every 5000 km/ 6 months*

**TRANSAXLE AUTOMATIC** 6/1  
Capacity: 6,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 4036**

*Check every 10000 km/ 12 months, change every 45000 km/ 30 months*

**HYDRAULIC BRAKE/CLUTCH SYSTEM**  
Capacity: 0,57 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4**

*Change every 20000 km/ 24 months*

**POWER STEERING**  
Capacity: 1,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**ATF Dexron II-D**

*Check every 5000 km/ 6 months*

**COOLING SYSTEM**  
Capacity: 5,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 12 EVO**

*Check every 10000 km/ 10 months, change every 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is*

PRODUCT RECOMMENDATION

# HAIMA (FAW) M5 M5 1.5T AT 6F24 (2014 AND AFTER)



*advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*