HAIMA (FAW) S5 S5 1.5T 6MT HMA7151GA4W (2014 AND AFTER)



ENGINE HMA GN15-TF Capacity: 4,9 liter, Filter capacity: 0,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Asyntho 5W-30		
Change every 5000 km/ 6 months		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Duranza LSP 5W-30		
Change every 5000 km/ 6 months		
USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1		
Asyntho 5W-30		
Change every 2500 km/ 2 months		
USE		CLIMATE
First change only		Cold
PRODUCT RECOMMENDATION 1		
Duranza LSP 5W-30		
Change every 2500 km/ 2 months		
TRANSAXLE MANUAL 6/1 Capacity: 1,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90

Syngear TDL 75W-90

SP Gear 1011

Syngear 75W-90

HAIMA (FAW) S5 S5 1.5T 6MT HMA7151GA4W (2014 AND AFTER)



HYDRAULIC BRAKE/CLUTCH SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
Check every 5000 km/ 6 months, change every 20000 km/ 24 months			

POWER STEERING Capacity: 1,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	
Check every 5000 km/ 6 months	'	,

COOLING SYSTEM Capacity: 8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 12 EVO		
Check every 10000 km/ 10 months.	change every 24 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.