## **VOLKSWAGEN (FAW) BORA 1J BORA 2.0** (2008-2010)



| Helar SP LL-03 5W-30              | Presteza MSP 5W-30       | Emperol 5W-40            |
|-----------------------------------|--------------------------|--------------------------|
| PRODUCT RECOMMENDATION 1          | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Initial service                   |                          | Moderate                 |
| USE                               |                          | CLIMATE                  |
| Change every 15000 km/ 12 month   | S                        |                          |
| Helar SP LL-03 5W-30              | Presteza MSP 5W-30       | Emperol 5W-40            |
| PRODUCT RECOMMENDATION 1          | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Normal                            |                          | Moderate                 |
| USE                               |                          | CLIMATE                  |
| ENGINE CEN<br>Capacity: 4,7 liter |                          |                          |

Change every 7500 km

| TRANSAXLE AUTOMATIC 6/1  |          |
|--------------------------|----------|
| USE                      | CLIMATE  |
| Normal                   | Moderate |
| PRODUCT RECOMMENDATION 1 |          |
| SP Matic 4026            |          |
| Check every 15000 km     |          |
| USE                      | CLIMATE  |

| USE                      | CLIMATE  |
|--------------------------|----------|
| Initial service          | Moderate |
| PRODUCT RECOMMENDATION 1 |          |
| SP Matic 4026            |          |
| Check every 7500 km      |          |

TRANSAXLE MANUAL 5/1 CLIMATE Normal Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 **SP Gear 1081** SP Gear 5015 Check every 15000 km USE CLIMATE Initial service Moderate **PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2** SP Gear 1081 SP Gear 5015

Check every 7500 km

## **VOLKSWAGEN (FAW) BORA 1J BORA 2.0** (2008-2010)



| HYDRAULIC BRAKE/CLUTCH SYSTEM          |                   |          |
|--|-------------------|----------|
| USE                                    |                   | CLIMATE  |
| Normal                                 |                   | Moderate |
| PRODUCT RECOMMENDATION 1               |                   |          |
| Drauliquid-LV Super DOT 4              |                   |          |
| Check every 15000 km/ 12 months, chang | e every 24 months |          |
| USE                                    |                   | CLIMATE  |
| Initial service                        |                   | Moderate |
|  |                   |          |

## **PRODUCT RECOMMENDATION 1** Drauliquid-LV Super DOT 4

Check every 7500 km

| POWER STEERING           |          |
|--------------------------|----------|
| USE                      | CLIMATE  |
| Normal                   | Moderate |
| PRODUCT RECOMMENDATION 1 |          |
| SP Fluid 3013            |          |
| Check every 15000 km     |          |

| Check | everv | 15000 | kn |
|-------|-------|-------|----|

| use<br>Initial service   | climate<br>Moderate |
|--------------------------|---------------------|
| PRODUCT RECOMMENDATION 1 |                     |
| SP Fluid 3013            |                     |
| Check every 7500 km      | ·                   |

| COOLING SYSTEM           |                          |                    |
|--------------------------|--------------------------|--------------------|
| use<br>Normal            |                          | сымате<br>Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |                    |
| Coolant SP 12            | Coolant SP 12 EVO        |                    |

Check every 15000 km

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Initial service          |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| Coolant SP 12            | Coolant SP 12 EVO        |          |
| Check every 7500 km      | 1                        | l        |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.