PRODUCT RECOMMENDATION

TOYOTA (GAC) HIGHLANDER
HIGHLANDER 2.0 T FWD (2015 AND AFTER)

ENGINE 8AR-FTS
Capacity: 4,9 liter, Filter capacity: 0,2 liter

USE		CLIMATE
Preferred		Moderate
PRODUCT RECOMMENDATION 1		
Presteza MSP 0W-20		

Change every 10000 km/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza ECO 5W-20	**Presteza MSP 5W-30**	**Xedoz FE 5W-30**

Change every 10000 km/ 12 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza ECO 5W-20	**Presteza MSP 5W-30**	**Xedoz FE 5W-30**

Change every 5000 km/ 6 months

USE		CLIMATE
Preferred, severe		Moderate
PRODUCT RECOMMENDATION 1		
Presteza MSP 0W-20		

Change every 5000 km/ 6 months

TRANSAXLE AUTOMATIC 6/1
Capacity: 6,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		

Check every 40000 km/ 24 months

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

TOYOTA (GAC) HIGHLANDER
HIGHLANDER 2.0 T FWD (2015 AND AFTER)

COOLING SYSTEM
Capacity: 11,04 liter, Capacity: 3,56 liter (+ intercooler)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 40000 km, change every 80000 km

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 40000 km, change every 160000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367