

HAVAL (CHN) HAVAL H6 1ST GEN HAVAL H6 2.4 (2011-2017)

**ENGINE 4G69S4M**

Capacity: 4,3 liter (Service fill), Filter capacity: 0,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar SP LL-03 5W-30	Presteza MSP 5W-30	Avanza RPC 5W-30

Change every 6000 km/ 6 months

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 0W-30	Avanza MSP 0W-30	Helar 0W-40

*Change every 6000 km/ 6 months***TRANSAXLE AUTOMATIC 4/1**

Capacity: 7,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4026		

*Check every 20000 km/ 12 months, change every 100000 km***HYDRAULIC BRAKE SYSTEM**

Capacity: 0,83 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 6000 km, change every 30000 km

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 6000 km, change every 40000 km

HAVAL (CHN) HAVAL H6 1ST GEN HAVAL H6 2.4 (2011-2017)



POWER STEERING

Capacity: 1,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

Check every 6000 km, change every 30000 km

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

Check every 6000 km, change every 40000 km

COOLING SYSTEM

Capacity: 7,45 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 300 km, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.