

PRODUCT RECOMMENDATION

KIA (DYK) K3S K3S 1.6 MPI (2014 AND AFTER)



ENGINE G4FG
Capacity: 3,3 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Emperol 10W-40	Bi-Turbo 15W-40	Bi-Turbo 20W-50

Change every 7500 km/ 6 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza ECO 5W-20	Presteza MSP 5W-30	Duranza LSP 5W-30

Change every 7500 km/ 6 months

TRANSAXLE AUTOMATIC 6/1
Capacity: 7,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		

Check every 10000 km/ 12 months, change every 40000 km/ 48 months

TRANSAXLE MANUAL 6/1
Capacity: 1,8-1,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Syngear 75W-90	

Check every 10000 km/ 12 months, change every 30000 km/ 36 months

HYDRAULIC BRAKE/CLUTCH SYSTEM
Capacity: 0,7-0,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Check every 5000 km/ 6 months

KIA (DYK) K3S K3S 1.6 MPI (2014 AND AFTER)



POWER STEERING

Capacity: 1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3013*Check every 5000 km/ 6 months*

COOLING SYSTEM

Capacity: 6,4 liter (with automatic transaxle), Capacity: 6,5 liter (with manual transaxle)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15+

PRODUCT RECOMMENDATION 2

Coolant SP 12*Change every 12 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.