MG MG3 MG3 1.3 (2011 AND AFTER)



ENGINE CSA7130 Capacity: 4,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Duranza LSP 5W-30	
Change every 10000 km/ 6 months	
USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
Duranza LSP 5W-30	
Change every 5000 km/ 6 months	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Duranza LSP 5W-30	
Change every 3000 km/ 3 months	
TRANSAXLE MANUAL 5/1 Capacity: 1,8 liter	

TRANSAXLE MANUAL 5/1 Capacity: 1,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 5015	
Change every 80000 km	,

HYDRAULIC BRAKE/CLUTCH SYST Capacity: 0,65-0,7 liter	ЕМ		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
Change every 24 months			

MG MG3 MG3 1.3 (2011 AND AFTER)



POWER STEERING Capacity: 0,92 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

COOLING SYSTEM Capacity: 5,6 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15+	Coolant SP 12		
Change every 80000 km/ 36 month	78	'	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.