

SHANGHAI MAPLE AUTOMOBILE HAIXUN

HAIXUN 1.5 (2006 AND AFTER)



ENGINE JL479QA
Capacity: 4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30

Change every 5000 km/ 3 months

TRANSAXLE MANUAL JL479QA 5/1
Capacity: 2,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-4 80W-90

Check every 10000 km/ 6 months, change every 40000 km

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-4 80W-90

Change every 5000 km

HYDRAULIC BRAKE SYSTEM
Capacity: 0,75 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

Change every 24 months

POWER STEERING
Capacity: 1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

PRODUCT RECOMMENDATION 2

ATF Almirol

Check every 5000 km/ 3 months, change every 20000 km

SHANGHAI MAPLE AUTOMOBILE HAIXUN

HAIXUN 1.5 (2006 AND AFTER)


COOLING SYSTEM

Capacity: 6 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26

Change every 40000 km/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.