SHANGHAI MAPLE AUTOMOBILE HUAPU HAIJING HUAPU HAIJING 1.8 (2009 AND



AFTER)

ENGINE JL481Q Capacity: 3,5 liter	
USE	CLIMATE
Normal	Tropical
PRODUCT RECOMMENDATION 1	
Bi-Turbo 20W-50	
Change every 5000 km/ 3 months	
USE	CLIMATE
Normal	Arctic
PRODUCT RECOMMENDATION 1	
Asyntho 5W-30	
Change every 5000 km/ 3 months	

USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube GL-4 80W-90	
Check every 10000 km/ 6 months, change every 40000	km
USE	CLIMATE
First change only	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube GL-4 80W-90	

HYDRAULIC BRAKE SYSTEM Capacity: 0,75 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Change every 24 months	,	·

SHANGHAI MAPLE AUTOMOBILE HUAPU HAIJING HUAPU HAIJING 1.8 (2009 AND



AFTER)

POWER STEERING Capacity: 1 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Matic 2032	ATF Almirol		
Chack every 5000 km/ 3 months, change every 20000 km			

Check every 5000 km/3 months, change every 20000 km

COOLING SYSTEM Capacity: 7,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
Change every 40000 km/24 months	'		

Change every 40000 km/24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.