

MITSUBISHI (SOUEAST) LANCER EX

LANCER EX 2.0 AT (2013 AND AFTER)



ENGINE 4B11
Capacity: 4,3 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50

Change every 10000 km/ 6 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Avanza MSP 0W-30

PRODUCT RECOMMENDATION 2

Emperol 5W-40

PRODUCT RECOMMENDATION 3

Asyntho 5W-30

Change every 10000 km/ 6 months

USE	CLIMATE
First change only	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50

Change every 1000 km

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

Avanza MSP 0W-30

PRODUCT RECOMMENDATION 2

Emperol 5W-40

PRODUCT RECOMMENDATION 3

Asyntho 5W-30

Change every 1000 km

TRANSAXLE CVT INVECS-III 1/1
Capacity: 7,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4016

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

HYDRAULIC BRAKE/CLUTCH SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

PRODUCT RECOMMENDATION 3

Drauliquid DOT 3

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

MITSUBISHI (SOUEAST) LANCER EX

LANCER EX 2.0 AT (2013 AND AFTER)



POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Check every 10000 km/ 6 months

COOLING SYSTEM

Capacity: 7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 12 EVO		

Change every 40000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.