

BRILLIANCE FRV/BS2 FRV / BS2 1.3 (63 KW) SY7130KSAA/KSBAA/FSBAA (2011 OG EFTER)



MOTOR 4G13S
Kapacitet: 4 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Asyntho 5W-30

PRODUKTANBEFALING 2

Emperol 10W-40

Skift alle 5000 km

ANVEND
Krævende

KLIMA
Moderat

PRODUKTANBEFALING 1

Asyntho 5W-30

PRODUKTANBEFALING 2

Emperol 10W-40

Skift alle 3000 km

TRANSAKSEL MANUEL 5/1
Kapacitet: 2,1 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

Kontroller alle 20000 km, skift alle 40000 km

ANVEND
Krævende

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

Kontroller alle 10000 km, skift alle 40000 km

ANVEND
Første Service

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

Kontroller alle 6000 km, skift alle 10000 km

BRILLIANCE FRV/BS2 FRV / BS2 1.3 (63 KW) SY7130KSAA/KSBAA/FSBAA (2011 OG EFTER)



HYDRAULISK BREMSESYSTEM

Kapacitet: 0,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Kontroller alle 10000 km/ 6 måneder, skift alle 40000 km/ 24 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Kontroller alle 10000 km/ 6 måneder, skift alle 30000 km/ 18 måneder

ANVEND	KLIMA
Krævende, første skift kun	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Kontroller alle 10000 km/ 6 måneder, skift alle 40000 km/ 24 måneder

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Kontroller alle 5000 km/ 3 måneder

SERVOSTYRING

Kapacitet: 0,9 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Matic 2032	ATF Almirol	

Kontroller alle 10000 km/ 6 måneder, skift alle 40000 km/ 24 måneder

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Matic 2032	ATF Almirol	

Kontroller alle 5000 km/ 3 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.