

# BUICK (SGM) LACROSSE LACROSSE 3.0 V6 (2009-2011)



**ENGINE LF1**  
Capacity: 6,2 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1

**Presteza MSP 5W-30**

PRODUCT RECOMMENDATION 2

**Xedoz FE 5W-30**

*Check every 3000 km/ 1 months, change every 12 months*

**TRANSAXLE AUTOMATIC 6/1**  
Capacity: 8 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 4036**

*Change every 160000 km*

USE  
Severe

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 4036**

*Change every 80000 km*

## HYDRAULIC BRAKE SYSTEM

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

*Change every 30000 km/ 24 months*

## COOLING SYSTEM

Capacity: 7,8 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 15**

PRODUCT RECOMMENDATION 2

**Coolant SP 15+**

*Change every 240000 km/ 60 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*