

CHERY QQ3 QQ3 0.8 (2003-2015)



MOTOR SQR372

Kapacitet: 2,9 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Specialsynth MSP 5W-40	Emperol 5W-40	Asyntho 5W-30

Skift alle 5000 km/ 6 måneder

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1		
Duranza LSP 5W-30		

Skift alle 5000 km/ 6 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Specialsynth MSP 5W-40	Emperol 5W-40	Asyntho 5W-30

Skift alle 2500 km/ 3 måneder

ANVEND	KLIMA
Krævende	Arktisk

PRODUKTANBEFALING 1		
Duranza LSP 5W-30		

Skift alle 2500 km/ 3 måneder

TRANSAKSEL MANUEL QR512 5/1

Kapacitet: 2,1 liter (Førstegangsopfyldning), Kapacitet: 1 liter (Servicepåfyldning)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90

Skift alle 30000 km/ 12 måneder

CHERY QQ3 QQ3 0.8 (2003-2015)



HYDRAULISK BREMSE- & KOBLINGSSYSTEM

Kapacitet: 0,45 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Drauliquid DOT 3		

Skift alle 50000 km/ 24 måneder

ANVEND		KLIMA
Krævende		Moderat
PRODUKTANBEFALING 1		
Drauliquid DOT 3		

Skift alle 25000 km/ 12 måneder

SERVOSTYRING

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Matic 2032	ATF Almirol	

Skift alle 50000 km/ 24 måneder

KØLESYSTEM

Kapacitet: 3,8 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

Skift alle 40000 km/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.