

CHERY TIGGO / TIGGO 3 TIGGO 2.4 (2008-2013)



MOTOR 4G64S4M
Kapacitet: 4,3 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Emperol 10W-40

Skift alle 15000 km

ANVEND
Første Service

KLIMA
Moderat

PRODUKTANBEFALING 1

Emperol 10W-40

Skift alle 5000 km

TRANSAKSEL AUTOMATISK 4/1
Kapacitet: 6-6,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Matic 4026

TRANSAKSEL MANUEL 5/1
Kapacitet: 2,2 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

PRODUKTANBEFALING 3

Syngear 75W-90

Skift alle 30000 km/ 12 måneder

HYDRAULISK BREMSE- & KOBLINGSSYSTEM
Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Skift alle 50000 km/ 24 måneder

CHERY TIGGO / TIGGO 3 TIGGO 2.4 (2008-2013)



SERVOSTYRING

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 2032

PRODUKTANBEFALING 2

ATF Almirol

Kontroller alle 15000 km

KØLESYSTEM

Kapacitet: 7,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Skift alle 40000 km/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.