

CHERY TIGGO / TIGGO 3 TIGGO 3 1.6 (2013-2019)



MOTOR SQRE4G16
Kapacitet: 4 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Emperol 10W-40		

Skift alle 15000 km

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Helar MSP+ 5W-40	Specialsynth MSP 5W-40	Emperol 5W-40

Skift alle 15000 km

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1		
Emperol 10W-40		

Skift alle 5000 km

ANVEND	KLIMA
Første Service	Koldt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Helar MSP+ 5W-40	Specialsynth MSP 5W-40	Emperol 5W-40

Skift alle 5000 km

TRANSAKSEL CVT 1/1
Kapacitet: 8 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Matic 4026		

Kontroller alle 15000 km, skift alle 40000 km

TRANSAKSEL MANUEL 5/1
Kapacitet: 2,2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90

Kontroller alle 15000 km, skift alle 30000 km/ 12 måneder

CHERY TIGGO / TIGGO 3 TIGGO 3 1.6 (2013-2019)



HYDRAULISK BREMSE- & KOBLINGSSYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Skift alle 40000 km/ 24 måneder

SERVOSTYRING

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Matic 2032	ATF Almirol	

Skift alle 30000 km/ 24 måneder

KØLESYSTEM

Kapacitet: 7,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

Skift alle 40000 km/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.