

GEELY (GLEAGLE/ENGLON) HQ (HOAQING) HQ SRV (2003-2008)



MOTOR MR479Q
Kapacitet: 3,5 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Bi-Turbo 15W-40	Bi-Turbo 20W-50	

Skift alle 5000 km/ 6 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Asyntho 5W-30	Emperol 10W-40	

Skift alle 5000 km/ 6 måneder

TRANSAXSEL MANUEL 4/1

Kapacitet: 2,25 liter (Førstegangsupfyldning), Kapacitet: 2,1 liter (Servicepåfyldning)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube GL-4 80W-90		

Skift alle 40000 km/ 24 måneder

HYDRAULISK BREMSE- & KOBLINGSSYSTEM

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Drauliquid DOT 3		

Skift alle 12 måneder

SERVOSTYRING

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Skift alle 10000 km/ 6 måneder

GEELY (GLEAGLE/ENGLON) HQ (HOAQING) HQ SRV (2003-2008)



KØLESYSTEM

Kapacitet: 3,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Skift alle 40000 km/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.