

HAIMA (FAW) 7 7 2.0 TD (2012 OG EFTER)



MOTOR HM484Q

Kapacitet: 3,3 liter, Filterkapacitet: 0,3 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Asyntho 5W-30

Skift alle 5000 km/ 6 måneder

ANVEND	KLIMA
Første skift kun	Moderat

PRODUKTANBEFALING 1

Asyntho 5W-30

Skift alle 2500 km/ 2 måneder

TRANSAXEL AUTOMATISK 5F23 5/1

Kapacitet: 7,6 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

SP Matic 4026

Skift alle 50000 km/ 36 måneder

HYDRAULISK BREMSE- & KOBLINGSSYSTEM

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Drauliquid-S DOT 4

PRODUKTANBEFALING 2

Drauliquid DOT 3

Kontroller alle 5000 km/ 6 måneder, skift alle 20000 km/ 24 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1

Drauliquid-S DOT 4

PRODUKTANBEFALING 2

Drauliquid DOT 3

Skift alle 12 måneder

HAIMA (FAW) 7 7 2.0 TD (2012 OG EFTER)



SERVOSTYRING

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Kontroller alle 5000 km/ 6 måneder, skift alle 20000 km/ 24 måneder

KØLESYSTEM

Kapacitet: 6,2-6,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Kontroller alle 10000 km/ 10 måneder, skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.