

HAIMA (FAW) M5 M5 1.5T AT 6F24(2014 OG EFTER)



MOTOR HMA GN15-TF
Kapacitet: 4,6-5,3 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Asyntho 5W-30

Skift alle 5000 km/ 6 måneder

TRANSAKSEL AUTOMATISK 6/1
Kapacitet: 6,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Matic 4036

Kontroller alle 10000 km/ 12 måneder, skift alle 45000 km/ 30 måneder

HYDRAULISK BREMSE- & KOBLINGSSYSTEM
Kapacitet: 0,57 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Skift alle 20000 km/ 24 måneder

SERVOSTYRING
Kapacitet: 1,1 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Kontroller alle 5000 km/ 6 måneder

KØLESYSTEM
Kapacitet: 5,7 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Coolant SP 12 EVO

Kontroller alle 10000 km/ 10 måneder, skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is

PRODUKTANBEFALING

HAIMA (FAW) M5 M5 1.5T AT 6F24 (2014 OG EFTER)



advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.