

HAIMA (FAW) S5 S5 1.6 5MT HMA7161GA4W (2014 OG EFTER)



MOTOR HMA GN16-VF1

Kapacitet: 3,8 liter, Filterkapacitet: 0,2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Asyntho 5W-30

Skift alle 5000 km/ 6 måneder

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1

Duranza LSP 5W-30

Skift alle 5000 km/ 6 måneder

ANVEND	KLIMA
Første skift kun	Moderat

PRODUKTANBEFALING 1

Asyntho 5W-30

Skift alle 2500 km/ 2 måneder

ANVEND	KLIMA
Første skift kun	Koldt

PRODUKTANBEFALING 1

Duranza LSP 5W-30

Skift alle 2500 km/ 2 måneder

TRANSAKSEL MANUEL 5/1

Kapacitet: 1,9 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

PRODUKTANBEFALING 3

Syngear 75W-90

Kontroller alle 10000 km/ 12 måneder, skift alle 20000 km/ 24 måneder

ANVEND	KLIMA
Første skift kun	Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

PRODUKTANBEFALING 3

Syngear 75W-90

Skift alle 2500 km/ 2 måneder

HAIMA (FAW) S5 S5 1.6 5MT HMA7161GA4W (2014 OG EFTER)



HYDRAULISK BREMSE- & KOBLINGSSYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Kontroller alle 5000 km/ 6 måneder, skift alle 20000 km/ 24 måneder

SERVOSTYRING

Kapacitet: 1,1 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Matic 2032	ATF Almirol	

Kontroller alle 5000 km/ 6 måneder

KØLESYSTEM

Kapacitet: 6,8 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Coolant SP 12 EVO		

Kontroller alle 10000 km/ 10 måneder, skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.