

HYUNDAI (BEIJING) NF / YUXIANG NF / YUXIANG 2.0 (2005 OG EFTER)



MOTOR G4KA
Kapacitet: 4,3 liter

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1

Bi-Turbo 15W-40

Skift alle 5000 km

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Duranza ECO 5W-20

PRODUKTANBEFALING 2

Duranza LSP 5W-30

PRODUKTANBEFALING 3

Asyntho 5W-30

Skift alle 5000 km

TRANSAKSEL AUTOMATISK 4/1
Kapacitet: 7,8 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Matic 4026

Kontroller alle 20000 km, skift alle 100000 km

TRANSAKSEL MANUEL 5/1
Kapacitet: 1,9 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Syngear 75W-90

Kontroller alle 15000 km/ 12 måneder

HYDRAULISK BREMSE- & KOBLINGSSYSTEM

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

Kontroller alle 24 måneder/ 30000 km

HYUNDAI (BEIJING) NF / YUXIANG NF / YUXIANG 2.0 (2005 OG EFTER)



SERVOSTYRING

Kapacitet: 0,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Kontroller alle 15000 km/ 12 måneder

KØLESYSTEM

Kapacitet: 6-6,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Kontroller alle 15000 km/ 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.