

HYUNDAI (BEIJING) VELOSTER FS

VELOSTER 1.6 MPI (95 KW) (2011 OG EFTER)



MOTOR Gamma

Kapacitet: 3,3 liter (Servicepåfyldning), Kapacitet: 3,6 liter (Tør efterfyld), Filterkapacitet: 0,3 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1

Emperol 10W-40

Skift alle 5000 km/ 6 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Duranza ECO 5W-20

PRODUKTANBEFALING 2

Presteza MSP 5W-30

PRODUKTANBEFALING 3

Helar MSP+ 5W-40

Skift alle 5000 km/ 6 måneder

TRANSAKSEL AUTOMATISK 6/1

Kapacitet: 7,3 liter

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1

SP Matic 4036

Skift alle 90000 km

TRANSAKSEL MANUEL 6/1

Kapacitet: 1,8-1,9 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Syngear 75W-90

Kontroller alle 48 måneder/ 60000 km

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Syngear 75W-90

Skift alle 120000 km

HYUNDAI (BEIJING) VELOSTER FS VELOSTER 1.6 MPI (95 KW) (2011 OG EFTER)



HYDRAULISK BREMSE- & KOBLINGSSYSTEM

Kapacitet: 0,7-0,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

PRODUKTANBEFALING 3

Drauliquid DOT 3

Kontroller alle 15000 km/ 12 måneder

KØLESYSTEM

Kapacitet: 5 liter, Kapacitet: 5,2 liter (med automatisk transaksel)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Skift alle 30000 km/ 24 måneder

ANVEND

Første skift kun

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Kontroller alle 60000 km/ 48 måneder, skift alle 210000 km/ 120 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.