

KIA (DYK) K3 YD K3 1.6 MPI (2013 OG EFTER)



MOTOR y-1.6

Kapacitet: 3,6 liter (Servicepåfyldning), Kapacitet: 4 liter (Tør efterfyld), Filterkapacitet: 0,3 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Emperol 10W-40	Bi-Turbo 15W-40	Bi-Turbo 20W-50

Skift alle 7500 km/ 6 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Duranza ECO 5W-20	Presteza MSP 5W-30	Duranza LSP 5W-30

Skift alle 7500 km/ 6 måneder

ANVEND	KLIMA
Krævende	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Emperol 10W-40	Bi-Turbo 15W-40	Bi-Turbo 20W-50

Skift alle 5000 km/ 6 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Duranza ECO 5W-20	Presteza MSP 5W-30	Duranza LSP 5W-30

Skift alle 5000 km/ 6 måneder

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Emperol 10W-40	Bi-Turbo 15W-40	Bi-Turbo 20W-50

Skift alle 10000 km/ 6 måneder

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Duranza ECO 5W-20	Presteza MSP 5W-30	Duranza LSP 5W-30

Skift alle 10000 km/ 6 måneder

ANVEND	KLIMA
Startservice, svær belastning	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Emperol 10W-40	Bi-Turbo 15W-40	Bi-Turbo 20W-50

Skift alle 7500 km/ 6 måneder

KIA (DYK) K3 YD K3 1.6 MPI (2013 OG EFTER)



ANVEND		KLIMA
Startservice, svær belastning		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Duranza ECO 5W-20	Presteza MSP 5W-30	Duranza LSP 5W-30
Skift alle 7500 km/ 6 måneder		

TRANSAKSEL AUTOMATISK A6GF1 6/1 Kapacitet: 7,3 liter		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Matic 4036		

TRANSAKSEL MANUEL M6CF1 6/1 Kapacitet: 1,8-1,9 liter		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	Syngear 75W-90	
Kontroller alle 15000 km/ 12 måneder, skift alle 45000 km/ 36 måneder		

ANVEND		KLIMA
Krævende		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	Syngear 75W-90	
Kontroller alle 10000 km/ 12 måneder, skift alle 30000 km/ 36 måneder		

HYDRAULISK BREMSE- & KOBLINGSSYSTEM Kapacitet: 0,7-0,8 liter		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3
Kontroller alle 15000 km/ 12 måneder, skift alle 24 måneder		



KIA (DYK) K3 YD K3 1.6 MPI (2013 OG EFTER)



SERVOSTYRING

Kapacitet: 1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3013

KØLESYSTEM

Kapacitet: 6,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Skift alle 12 måneder

KLIMAANLÆGSKOMPRESSOR

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

KLIMAANLÆGSSYSTEM R-1234yf

Kapacitet: 530 gram

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

KLIMAANLÆGSSYSTEM R-134a

Kapacitet: 530 gram

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.