

KIA (DYK) K3S K3S 1.6 MPI (2014 OG EFTER)



MOTOR G4FG
Kapacitet: 3,3 liter

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1

Emperol 10W-40

PRODUKTANBEFALING 2

Bi-Turbo 15W-40

PRODUKTANBEFALING 3

Bi-Turbo 20W-50

Skift alle 7500 km/ 6 måneder

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Duranza ECO 5W-20

PRODUKTANBEFALING 2

Presteza MSP 5W-30

PRODUKTANBEFALING 3

Duranza LSP 5W-30

Skift alle 7500 km/ 6 måneder

TRANSAKSEL AUTOMATISK 6/1
Kapacitet: 7,3 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Matic 4036

Kontroller alle 10000 km/ 12 måneder, skift alle 40000 km/ 48 måneder

TRANSAKSEL MANUEL 6/1
Kapacitet: 1,8-1,9 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Syngear 75W-90

Kontroller alle 10000 km/ 12 måneder, skift alle 30000 km/ 36 måneder

HYDRAULISK BREMSE- & KOBLINGSSYSTEM
Kapacitet: 0,7-0,8 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

PRODUKTANBEFALING 3

Drauliquid DOT 3

Kontroller alle 5000 km/ 6 måneder

KIA (DYK) K3S K3S 1.6 MPI (2014 OG EFTER)



SERVOSTYRING

Kapacitet: 1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3013

Kontroller alle 5000 km/ 6 måneder

KØLESYSTEM

Kapacitet: 6,4 liter (med automatisk transaksel), Kapacitet: 6,5 liter (med manuel transaksel)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Skift alle 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.