

KIA (DYK) SPORTAGE SL SPORTAGE 2.0 AWD (2010 OG EFTER)



MOTOR G4GC
Kapacitet: 4 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Bi-Turbo 15W-40	Bi-Turbo 20W-50

Skift alle 7500 km/ 6 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Duranza ECO 5W-20	Asyntho 5W-30	Emperol 10W-40

Skift alle 7500 km/ 6 måneder

ANVEND	KLIMA
Krævende	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Bi-Turbo 15W-40	Bi-Turbo 20W-50

Skift alle 5000 km/ 6 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Duranza ECO 5W-20	Asyntho 5W-30	Emperol 10W-40

Skift alle 5000 km/ 6 måneder

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Bi-Turbo 15W-40	Bi-Turbo 20W-50

Skift alle 10000 km/ 6 måneder

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Duranza ECO 5W-20	Asyntho 5W-30	Emperol 10W-40

Skift alle 10000 km/ 6 måneder

ANVEND	KLIMA
Startservice, svær belastning	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Bi-Turbo 15W-40	Bi-Turbo 20W-50

Skift alle 7500 km/ 6 måneder

KIA (DYK) SPORTAGE SL SPORTAGE 2.0 AWD (2010 OG EFTER)



ANVEND		KLIMA
Startservice, svær belastning		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Duranza ECO 5W-20	Asyntho 5W-30	Emperol 10W-40
Skift alle 7500 km/ 6 måneder		

DIFFERENTIALE BAG Kapacitet: 0,75 liter		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Gearlube GL-5 80W-90		
Kontroller alle 40000 km, skift alle 100000 km		

ANVEND		KLIMA
Krævende		Moderat
PRODUKTANBEFALING 1		
Gearlube GL-5 80W-90		
Skift alle 80000 km		

REDUKTIONSGEARKASSE Kapacitet: 0,8 liter		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Gearlube GL-5 80W-90		
Kontroller alle 40000 km, skift alle 100000 km		

ANVEND		KLIMA
Krævende		Moderat
PRODUKTANBEFALING 1		
Gearlube GL-5 80W-90		
Skift alle 80000 km		



KIA (DYK) SPORTAGE SL SPORTAGE 2.0 AWD (2010 OG EFTER)



TRANSAKSEL MANUEL 5/1

Kapacitet: 2,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

PRODUKTANBEFALING 3

Syngear 75W-90

Kontroller alle 15000 km/ 12 måneder, skift alle 45000 km/ 36 måneder

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

PRODUKTANBEFALING 3

Syngear 75W-90

Kontroller alle 10000 km/ 12 måneder, skift alle 30000 km/ 36 måneder

HYDRAULISK BREMSESYSTEM

Kapacitet: 0,7-0,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

PRODUKTANBEFALING 3

Drauliquid DOT 3

Skift alle 5000 km/ 6 måneder

SERVOSTYRING

Kapacitet: 0,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Skift alle 5000 km/ 6 måneder

KØLESYSTEM

Kapacitet: 7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Skift alle 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.