

LIFAN 620 / SOLANO 620 / SOLANO 1.6 (2010 OG EFTER)



MOTOR LF481Q3
Kapacitet: 4 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Asyntho 5W-30

PRODUKTANBEFALING 2

Bi-Turbo 15W-40

Skift alle 8000 km

TRANSAKSEL CVT RD CVT150 1/1
Kapacitet: 4 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Matic 4016

Skift alle 90000 km/ 24 måneder

TRANSAKSEL MANUEL 5/1
Kapacitet: 2,1 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

Skift alle 90000 km/ 24 måneder

HYDRAULISK BREMSE- & KOBLINGSSYSTEM
Kapacitet: 0,72 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Skift alle 50000 km/ 24 måneder

SERVOSTYRING
Kapacitet: 0,83 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Skift alle 50000 km/ 24 måneder

LIFAN 620 / SOLANO 620 / SOLANO 1.6 (2010 OG EFTER)



KØLESYSTEM

Kapacitet: 8,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Skift alle 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.