

MITSUBISHI (SOUEAST) LANCER FORTIS

LANCER FORTIS 1.6 (2013 OG EFTER)



MOTOR 4A92
Kapacitet: 4 liter

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1

Bi-Turbo 20W-50

Skift alle 10000 km/ 6 måneder

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Avanza MSP 0W-30

PRODUKTANBEFALING 2

Emperol 5W-40

PRODUKTANBEFALING 3

Asyntho 5W-30

Skift alle 10000 km/ 6 måneder

ANVEND
Første skift kun

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1

Bi-Turbo 20W-50

Skift alle 1000 km

ANVEND
Første skift kun

KLIMA
Moderat

PRODUKTANBEFALING 1

Avanza MSP 0W-30

PRODUKTANBEFALING 2

Emperol 5W-40

PRODUKTANBEFALING 3

Asyntho 5W-30

Skift alle 1000 km

TRANSAKSEL MANUEL F5MBB 5/1
Kapacitet: 2,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Gear 5015

Kontroller alle 10000 km/ 6 måneder, skift alle 20000 km/ 12 måneder

ANVEND
Krævende

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Gear 5015

Skift alle 10000 km/ 6 måneder

MITSUBISHI (SOUEAST) LANCER FORTIS

LANCER FORTIS 1.6 (2013 OG EFTER)



HYDRAULISK BREMSE- & KOBLINGSSYSTEM

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

PRODUKTANBEFALING 3

Drauliquid DOT 3

Kontroller alle 10000 km/ 6 måneder, skift alle 40000 km/ 24 måneder

SERVOSTYRING

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Matic 2032

PRODUKTANBEFALING 2

ATF Almirol

PRODUKTANBEFALING 3

ATF Dexron II-D

Kontroller alle 10000 km/ 6 måneder

KØLESYSTEM

Kapacitet: 4-7 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Coolant SP 12 EVO

Skift alle 40000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.