

PEUGEOT (DONGFENG) 408 408 1.6 (78 KW) (2010 OG EFTER)



MOTOR TU5JP4
Kapacitet: 3,25 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Presteza MSP 0W-30

PRODUKTANBEFALING 2
Duranza LSP 5W-30

Skift alle 7500 km/ 6 måneder

TRANSAKSEL AUTOMATISK AL4 4/1
Kapacitet: 3 liter (Servicepåfyldning), Kapacitet: 5,85 liter (Tør efterfyld)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Matic 2032

ANVEND
Krævende

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Matic 2032

Skift alle 90000 km/ 72 måneder

TRANSAKSEL MANUEL 5/1
Kapacitet: 1,9 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Gear 5015

Skift alle 60000 km/ 48 måneder

HYDRAULISK BREMSE- & KOBLINGSSYSTEM

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2
Drauliquid-S DOT 4

Kontroller alle 7500 km/ 6 måneder, skift alle 24 måneder

PEUGEOT (DONGFENG) 408 408 1.6 (78 KW) (2010 OG EFTER)



SERVOSTYRING

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Kontroller alle 7500 km/ 6 måneder

KØLESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 14+

Kontroller alle 7500 km/ 6 måneder, skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.