

PORSCHE (CHN) CAYMAN 981 CAYMAN 98711X (2006 OG EFTER)



MOTOR M 97/20

Kapacitet: 7,75 liter, Filterkapacitet: 0,25 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Specialsynth MSP 5W-40	Helar 0W-40	Emperol 5W-40

Skift alle 10000 km/ 12 måneder

DIFFERENTIALE FRA EN AUTOMATISK

Kapacitet: 0,8 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 1011	Syngear TDL 75W-90	

Skift alle 180000 km/ 120 måneder

GEAR AUTOMATISK Tiptronic S 5/1

Kapacitet: 3,5 liter (Servicepåfyldning), Kapacitet: 9 liter (Tør efterfyld)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Matic 2032		

Skift alle 180000 km/ 120 måneder

TRANSAKSEL MANUEL 5/1

Kapacitet: 2,25 liter (Servicepåfyldning), Kapacitet: 3,2 liter (Tør efterfyld)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 1011	Syngear TDL 75W-90	

Skift alle 180000 km/ 120 måneder

HYDRAULISK BREMSE- & KOBLINGSSYSTEM

Kapacitet: 0,4 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Drauliquid-LV Super DOT 4		

Kontroller alle 24 måneder/ 30000 km

PORSCHE (CHN) CAYMAN 981 CAYMAN 98711X (2006 OG EFTER)



SERVOSTYRING

Kapacitet: 1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3013

KØLESYSTEM

Kapacitet: 22 liter, Kapacitet: 22,4 liter (+ automatisk transmission/transaksel)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Kontroller alle 24 måneder/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.