

ROEWE 750 750 2.5 CSA7250AC (2009 OG EFTER)



MOTOR 25K4F
Kapacitet: 6 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Emperol 5W-40	Asyntho 5W-30	

Skift alle 5000 km/ 6 måneder

TRANSAKSEL AUTOMATISK 5/1
Kapacitet: 8,1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Matic 4026		

Skift alle 10000 km/ 6 måneder

ANVEND	KLIMA
Første skift kun	Moderat

PRODUKTANBEFALING 1		
SP Matic 4026		

Skift alle 5000 km

HYDRAULISK BREMSESYSYSTEM
Kapacitet: 0,55 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Skift alle 24 måneder

KRAFTSYSTEM
Kapacitet: 1,25 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Matic 2032	ATF Almirol	

Kontroller alle 5000 km/ 3 måneder, skift alle 20000 km

ROEWE 750 750 2.5 CSA7250AC (2009 OG EFTER)



KØLESYSTEM

Kapacitet: 8,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Skift alle 40000 km/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.