

SHANGHAI MAPLE AUTOMOBILE HAIXUN

HAIXUN 1.5 (2006 OG EFTER)



MOTOR JL479QA
Kapacitet: 4 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Asyntho 5W-30

Skift alle 5000 km/ 3 måneder

TRANSAKSEL MANUEL JL479QA 5/1
Kapacitet: 2,1 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

Kontroller alle 10000 km/ 6 måneder, skift alle 40000 km

ANVEND
Første skift kun

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

Skift alle 5000 km

HYDRAULISK BREMSESYSYSTEM
Kapacitet: 0,75 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Skift alle 24 måneder

SERVOSTYRING
Kapacitet: 1 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Matic 2032

PRODUKTANBEFALING 2

ATF Almirol

Kontroller alle 5000 km/ 3 måneder, skift alle 20000 km

SHANGHAI MAPLE AUTOMOBILE HAIXUN

HAIXUN 1.5 (2006 OG EFTER)



KØLESYSTEM

Kapacitet: 6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Skift alle 40000 km/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.