

TOYOTA (GAC) HIGHLANDER

HIGHLANDER 2.0 T FWD (2015 OG EFTER)



MOTOR 8AR-FTS

Kapacitet: 4,9 liter, Filterkapacitet: 0,2 liter

ANVEND

Foretrukne

KLIMA

Moderat

PRODUKTANBEFALING 1

Presteza MSP 0W-20

Skift alle 10000 km/ 12 måneder

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Duranza ECO 5W-20

PRODUKTANBEFALING 2

Presteza MSP 5W-30

PRODUKTANBEFALING 3

Xedoz FE 5W-30

Skift alle 10000 km/ 12 måneder

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

Duranza ECO 5W-20

PRODUKTANBEFALING 2

Presteza MSP 5W-30

PRODUKTANBEFALING 3

Xedoz FE 5W-30

Skift alle 5000 km/ 6 måneder

ANVEND

Foretrukken, alvorlig

KLIMA

Moderat

PRODUKTANBEFALING 1

Presteza MSP 0W-20

Skift alle 5000 km/ 6 måneder

TRANSAKSEL AUTOMATISK 6/1

Kapacitet: 6,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4036

Kontroller alle 40000 km/ 24 måneder

HYDRAULISK BREMSESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

Kontroller alle 10000 km/ 6 måneder, skift alle 40000 km/ 24 måneder

TOYOTA (GAC) HIGHLANDER

HIGHLANDER 2.0 T FWD (2015 OG EFTER)



KØLESYSTEM

Kapacitet: 11,04 liter, Kapacitet: 3,56 liter (+ mellemkøler)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Coolant SP 14+		

Kontroller alle 40000 km, skift alle 80000 km

ANVEND	KLIMA
Første skift kun	Moderat

PRODUKTANBEFALING 1		
Coolant SP 14+		

Kontroller alle 40000 km, skift alle 160000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.