

AICHI BOMLØFTER MED LARVEBÅND. RZ/SR/ISR SR182 ISUZU 4BD1 (1997-2002)



MOTOR Isuzu 4BD1

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra FE 5W-30	Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40

Skift alle 250 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra FE 5W-30	Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40

Skift alle 50 timer

HYDRAULISK SYSTEM

Kapacitet: 250 liter (Hydrauliktank)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus Biosynth 32	Perlus H 32	

Skift alle 1200 timer/ 12 måneder

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1		
Perlus H 15		

Skift alle 1200 timer/ 12 måneder

SMØREPUNKTER/NIPLER GENERELT

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 100 timer

KØLESYSTEM

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Coolant -38 Organic NF		

AICHI BOMLØFTER MED LARVEBÅND. RZ/SR/ISR SR182 ISUZU 4BD1 (1997-2002)



KØREREDUKTIONSGEARKASSE

Kapacitet: 3,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Multifleet SCD 30*Skift alle 1200 timer/ 12 måneder*

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1

Multifleet SCD 30*Skift alle 3 måneder/ 300 timer*

SVINGREDUKTIONSGEARKASSE

Kapacitet: 1,1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Abacot MEP 460*Skift alle 1200 timer/ 12 måneder*

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1

Abacot MEP 460*Skift alle 3 måneder/ 300 timer*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.