

# AICHI BOMLØFTERE MED HJUL SP/ISP SP25B ISUZU CC-4JG1



**MOTOR** Isuzu 4JG1  
Kapacitet: 7,5 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1                 | PRODUKTANBEFALING 2          | PRODUKTANBEFALING 3           |
|-------------------------------------|------------------------------|-------------------------------|
| <b>Agrisynth LSP Ultra FE 5W-30</b> | <b>Agridiesel MSP 15W-40</b> | <b>Agridiesel CRD+ 15W-40</b> |

Skift alle 250 timer

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

| PRODUKTANBEFALING 1                 | PRODUKTANBEFALING 2          | PRODUKTANBEFALING 3           |
|-------------------------------------|------------------------------|-------------------------------|
| <b>Agrisynth LSP Ultra FE 5W-30</b> | <b>Agridiesel MSP 15W-40</b> | <b>Agridiesel CRD+ 15W-40</b> |

Skift alle 50 timer

**HYDRAULISK SYSTEM**  
Kapacitet: 150 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1 |  |  |
|---------------------|--|--|
| <b>Perlus H 22</b>  |  |  |

Skift alle 1200 timer/ 12 måneder

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Arktisk |

| PRODUKTANBEFALING 1 |  |  |
|---------------------|--|--|
| <b>Perlus H 15</b>  |  |  |

Skift alle 1200 timer/ 12 måneder

**SMØREPUNKTER/NIPLER GENERELT**

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
|----------------------|---------------------------------|------------------------------|
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

Skift alle 100 timer

# AICHI BOMLØFTERE MED HJUL SP/ISP SP25B ISUZU CC-4JG1



## KØLESYSTEM

Kapacitet: 4,5 liter (Motor kun)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Coolant -38 Organic NF**

## KØREREDUKTIONSGEARKASSE

Kapacitet: 1,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Gearlube GL-4 80W-90**

PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

*Skift alle 1200 timer/ 12 måneder*

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

**Gearlube GL-4 80W-90**

PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

*Skift alle 3 måneder/ 300 timer*

## SVINGREDUKTIONSGEARKASSE

Kapacitet: 1,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Gearlube GL-4 80W-90**

PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

*Skift alle 1200 timer/ 12 måneder*

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

**Gearlube GL-4 80W-90**

PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

*Skift alle 3 måneder/ 300 timer*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*