

AMKODOR LÆSSERE, SKID-STEER 211T MMZ D-243



MOTOR MMZ D-243

Kapacitet: 15 liter

ANVEND		KLIMA
Normal, svovlniveau i brændstof <0,5 %, omgivelsestemperatur >-10° C		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP 10W-40	Kroontrak CVT 10W-40	Agrisynth MSP 10W-40

Skift alle 250 timer

ANVEND		KLIMA
Normal, svovlniveau i brændstof <0,5 %, omgivelsestemperatur >-10° C		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Asyntho 5W-30	Armado Synth 5W-30	

Skift alle 250 timer

DREVPUMPEGEAR

Kapacitet: 1,5 liter

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP 10W-40	Kroontrak CVT 10W-40	Agrisynth MSP 10W-40

Skift alle 400000 km/ 48 måneder

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Asyntho 5W-30	Armado Synth 5W-30	

Skift alle 400000 km/ 48 måneder

DRIVKÆDE

Kapacitet: 2 kg

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

NAVREDUKTIONER MED BREMSE BAG

Kapacitet: 3 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 400000 km/ 48 måneder

AMKODOR LÆSSERE, SKID-STEER 211T MMZ D-243



NAVREDUKTIONER FOR

Kapacitet: 3,4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90*Skift alle 400000 km/ 48 måneder*

HYDRAULISK SYSTEM

Kapacitet: 75 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Perlus Biosynth 46

PRODUKTANBEFALING 2

Perlus H 46*Skift alle 2000 timer*

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus Biosynth 32

PRODUKTANBEFALING 2

Perlus H 32*Skift alle 2000 timer*

SMØREPUNKTER/NIPLER GENERELT

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 20 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF*Skift alle 24 måneder*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.