

AMMANN ENKELTTROMLERULLER ASC

ASC 250 HT CUMMINS TIER 3



MOTOR Cummins QSB6.7-C220
Kapacitet: 19,7 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Agridiesel MSP 15W-40

PRODUKTANBEFALING 2

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 3

Synfleet SHPD 10W-40

Kontroller alle 20 timer, skift alle 6 måneder/ 500 timer

GEAR TROMLEDREV
Kapacitet: 7,7 liter

ANVEND
Normal

KLIMA
Tropisk

PRODUKTANBEFALING 1

Gearlube HS GL-5 80W-140

Kontroller alle 3 måneder/ 250 timer, skift alle 12 måneder/ 1000 timer

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 3 måneder/ 250 timer, skift alle 12 måneder/ 1000 timer

ANVEND
Første Service

KLIMA
Tropisk

PRODUKTANBEFALING 1

Gearlube HS GL-5 80W-140

Skift alle 100 timer

ANVEND
Første Service

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 100 timer

AMMANN ENKELTTROMLERULLER ASC

ASC 250 HT CUMMINS TIER 3



HJULGEAR

Kapacitet: 4,4 liter (hvert)

ANVEND	KLIMA
Normal	Tropisk

PRODUKTANBEFALING 1		
Gearlube HS GL-5 80W-140		

Kontroller alle 3 måneder/ 250 timer, skift alle 12 måneder/ 1000 timer

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 3 måneder/ 250 timer, skift alle 12 måneder/ 1000 timer

ANVEND	KLIMA
Første Service	Tropisk

PRODUKTANBEFALING 1		
Gearlube HS GL-5 80W-140		

Skift alle 100 timer

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 100 timer

HYDRAULISK SYSTEM

Kapacitet: 100 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 46	Perlus H 68	

Kontroller alle 20 timer, skift alle 24 måneder/ 2000 timer

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1		
Perlus H 32		

Kontroller alle 20 timer, skift alle 24 måneder/ 2000 timer

AMMANN ENKELTTROMLERULLER ASC

ASC 250 HT CUMMINS TIER 3



SMØREPUNKTER/NIPLER		
ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 HT Q9 High Grade Grease	PRODUKTANBEFALING 2 Labora Grease	PRODUKTANBEFALING 3 Q5 MP Calcep Grease EP 2
<i>Skift alle 250 timer/ 3 måneder</i>		

KØLESYSTEM Kapacitet: 30 liter		
ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Coolant SP 15+	PRODUKTANBEFALING 2 Coolant SP 12	PRODUKTANBEFALING 3 Coolant -38 Organic NF
<i>Kontroller alle 20 timer, skift alle 24 måneder/ 2000 timer</i>		

VIBRERENDE TROMLE FOR Kapacitet: 8 liter		
ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Agridiesel MSP 15W-40	PRODUKTANBEFALING 2 Agridiesel CRD+ 15W-40	PRODUKTANBEFALING 3 Synfleet SHPD 10W-40
<i>Kontroller alle 250 timer/ 3 måneder, skift alle 24 måneder/ 2000 timer</i>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.