

AMMANN ENKELTTROMLERULLER ASC

ASC 90 CUMMINS TIER 3



MOTOR Cummins QSB3.3-C99
Kapacitet: 7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40

Kontroller alle 20 timer, skift alle 3 måneder/ 250 timer

GEAR TROMLEDREV
Kapacitet: 2,5-2,8 liter

ANVEND	KLIMA
Normal	Tropisk

PRODUKTANBEFALING 1		
Gearlube HS GL-5 80W-140		

Kontroller alle 3 måneder/ 250 timer, skift alle 12 måneder/ 1000 timer

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 3 måneder/ 250 timer, skift alle 12 måneder/ 1000 timer

ANVEND	KLIMA
Første Service	Tropisk

PRODUKTANBEFALING 1		
Gearlube HS GL-5 80W-140		

Skift alle 100 timer

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 100 timer

AMMANN ENKELTTROMLERULLER ASC

ASC 90 CUMMINS TIER 3



HJULGEAR

Kapacitet: 2,5 liter (hvert)

ANVEND	KLIMA
Normal	Tropisk

PRODUKTANBEFALING 1		
Gearlube HS GL-5 80W-140		

Kontroller alle 3 måneder/ 250 timer, skift alle 12 måneder/ 1000 timer

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 3 måneder/ 250 timer, skift alle 12 måneder/ 1000 timer

ANVEND	KLIMA
Første Service	Tropisk

PRODUKTANBEFALING 1		
Gearlube HS GL-5 80W-140		

Skift alle 100 timer

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 100 timer

HYDRAULISK SYSTEM

Kapacitet: 73 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 46	Perlus H 68	

Kontroller alle 20 timer, skift alle 24 måneder/ 2000 timer

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1		
Perlus H 32		

Kontroller alle 20 timer, skift alle 24 måneder/ 2000 timer

AMMANN ENKELTTROMLERULLER ASC

ASC 90 CUMMINS TIER 3



SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
HT Q9 High Grade Grease	Labora Grease	Q5 MP Calcep Grease EP 2

Skift alle 250 timer/ 3 måneder

KØLESYSTEM

Kapacitet: 24 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Kontroller alle 20 timer, skift alle 24 måneder/ 2000 timer

VIBRERENDE TROMLE FOR

Kapacitet: 6,7 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40

Kontroller alle 250 timer/ 3 måneder, skift alle 24 måneder/ 2000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.