

AMMANN TANDEMTRÖMLER AV AV 95-2K CUMMINS TIER 1



MOTOR Cummins C3.3-C85
Kapacitet: 8 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agridiesel MSP 15W-40

PRODUKTANBEFALING 2
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 3
Synfleet SHPD 10W-40

Kontroller alle 20 timer, skift alle 3 måneder/ 250 timer

HYDRAULISK SYSTEM
Kapacitet: 65 liter

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Perlus H 46

PRODUKTANBEFALING 2
Perlus H 68

Kontroller alle 20 timer, skift alle 24 måneder/ 2000 timer

ANVEND
Normal

KLIMA
Arktisk

PRODUKTANBEFALING 1
Perlus H 32

Kontroller alle 20 timer, skift alle 24 måneder/ 2000 timer

SMØREPUNKTER/NIPLER

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
HT Q9 High Grade Grease

PRODUKTANBEFALING 2
Labora Grease

PRODUKTANBEFALING 3
Q5 MP Calcep Grease EP 2

Skift alle 250 timer/ 3 måneder

KØLESYSTEM
Kapacitet: 18 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Coolant SP 15+

PRODUKTANBEFALING 2
Coolant SP 12

PRODUKTANBEFALING 3
Coolant -38 Organic NF

Kontroller alle 20 timer, skift alle 24 måneder/ 2000 timer

AMMANN TANDEMTROMLER AV AV 95-2K CUMMINS TIER 1



VIBRERENDE TROMLE BAG

Kapacitet: 2 liter (hvert)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agridiesel MSP 15W-40

PRODUKTANBEFALING 2

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 3

Synfleet SHPD 10W-40

Kontroller alle 3 måneder/ 250 timer, skift alle 12 måneder/ 1000 timer

VIBRERENDE TROMLE FOR

Kapacitet: 4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agridiesel MSP 15W-40

PRODUKTANBEFALING 2

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 3

Synfleet SHPD 10W-40

Kontroller alle 3 måneder/ 250 timer, skift alle 12 måneder/ 1000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.