

ATLAS GMBH GRAVEMASKINER MED HJUL 5005M/MI (500) DEUTZ BF6M 1013 FC (2001-2004)



MOTOR Deutz BF6M-1013FC
Kapacitet: 21 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Skift alle 500 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Skift alle 50 timer

GEAR

ANVEND	KLIMA
Normal	Tropisk

PRODUKTANBEFALING 1		
Gearlube GL-5 85W-140		

Skift alle 1000 timer

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 1000 timer

ANVEND	KLIMA
Første Service	Tropisk

PRODUKTANBEFALING 1		
Gearlube GL-5 85W-140		

Skift alle 500 timer

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 500 timer

ATLAS GMBH GRAVEMASKINER MED HJUL 5005M/MI (500) DEUTZ BF6M 1013 FC (2001-2004)



HYDRAULISK SYSTEM

Kapacitet: 720 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 20W-20

Skift alle 3000 timer

ANVEND

Normal

KLIMA

Koldt

PRODUKTANBEFALING 1

Multifleet SCD 10W

Skift alle 3000 timer

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2

SMØREPUNKTER/NIPLER SVINGKRANSTÆNDER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Compound OGL EP 0/1

KØLESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 11

Skift alle 2000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.