

ATLAS GMBH GRAVEMASKINER MED HJUL 5205M (525)



MOTOR

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Skift alle 500 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Skift alle 50 timer

HYDRAULISK SYSTEM

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1		
Multifleet SCD 20W-20		

Skift alle 3000 timer

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1		
Multifleet SCD 10W		

Skift alle 3000 timer

SMØREPUNKTER/NIPLER ANDRE

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
MoS2 Grease EP 2		

SMØREPUNKTER/NIPLER SVINGKRANSTÆNDER

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Compound OGL EP 0/1		

ATLAS GMBH GRAVEMASKINER MED HJUL 5205M (525)



KØLESYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Coolant SP 11		

Skift alle 2000 timer

SVINGREDUKTIONSENHED

ANVEND		KLIMA
Normal		Tropisk
PRODUKTANBEFALING 1		
Gearlube GL-5 85W-140		

Skift alle 1000 timer

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 1000 timer

ANVEND		KLIMA
Første Service		Tropisk
PRODUKTANBEFALING 1		
Gearlube GL-5 85W-140		

Skift alle 50 timer

ANVEND		KLIMA
Første Service		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 50 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.