

# AUSA MULTITRANS DV DV 17



## MOTOR Isuzu

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

|                          |  |  |
|--------------------------|--|--|
| PRODUKTANBEFALING 1      |  |  |
| <b>Multifleet SCD 30</b> |  |  |

*Skift alle 100 timer*

| ANVEND | KLIMA |
|--------|-------|
| Normal | Koldt |

|                              |  |  |
|------------------------------|--|--|
| PRODUKTANBEFALING 1          |  |  |
| <b>Multifleet SCD 20W-20</b> |  |  |

*Skift alle 100 timer*

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

|                          |  |  |
|--------------------------|--|--|
| PRODUKTANBEFALING 1      |  |  |
| <b>Multifleet SCD 30</b> |  |  |

*Skift alle 50 timer*

| ANVEND         | KLIMA |
|----------------|-------|
| Første Service | Koldt |

|                              |  |  |
|------------------------------|--|--|
| PRODUKTANBEFALING 1          |  |  |
| <b>Multifleet SCD 20W-20</b> |  |  |

*Skift alle 50 timer*

## GEARKASSE DIFFERENTIALE REDUKTIONSENHED

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

|                             |                                    |  |
|-----------------------------|------------------------------------|--|
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |  |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

*Skift alle 1000 timer*

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

|                             |                                    |  |
|-----------------------------|------------------------------------|--|
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |  |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

*Skift alle 50 timer*



## HYDRAULISK SYSTEM

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1 |  |  |
|---------------------|--|--|
| <b>Perlus H 68</b>  |  |  |

*Skift alle 1000 timer*

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

| PRODUKTANBEFALING 1 |  |  |
|---------------------|--|--|
| <b>Perlus H 68</b>  |  |  |

*Skift alle 100 timer*

## SMØREPUNKTER/NIPLER

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
|----------------------|---------------------------------|------------------------------|
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

*Skift alle 50 timer*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*