

AUSA TIPVOGNE 108 DH PERKINS 103-07 (1994-2004)



MOTOR Perkins 103-07 (KL)
Kapacitet: 2,8 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	Multifleet SCD 30

Skift alle 150 timer

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1		
Multifleet SCD 20W-20		

Skift alle 150 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	Multifleet SCD 30

Skift alle 50 timer

ANVEND	KLIMA
Første Service	Koldt

PRODUKTANBEFALING 1		
Multifleet SCD 20W-20		

Skift alle 50 timer

GEAR DIFFERENTIALE
Kapacitet: 2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

Skift alle 900 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

Skift alle 50 timer

AUSA TIPVOGNE 108 DH PERKINS 103-07 (1994-2004)



HYDRAULISK SYSTEM

Kapacitet: 16,5 liter (Hydrauliktank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 68

Skift alle 900 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 68

Skift alle 150 timer

HYDRAULISK BREMSESYSTEM

Kapacitet: 0,25 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-S DOT 4

Skift alle 1000 timer

LEDFORBINDELSER

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Skift alle 50 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.