

BARFORD DUMPERE SX6000 IVECO N45MSSX00 (2007 OG EFTER)



MOTOR Iveco N45 MSSX00

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

Skift alle 300 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrisynth LSP Ultra 10W-40

PRODUKTANBEFALING 2

Agrisynth LSP 10W-40

PRODUKTANBEFALING 3

Armado Synth LSP Ultra 10W-40

Skift alle 300 timer

DIFFERENTIALE BAG

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 600 timer

DIFFERENTIALE FOR

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 600 timer

GEAR PowerShuttle/ITL

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF-F (Ford)

Skift alle 1200 timer/ 12 måneder

BARFORD DUMPERE SX6000 IVECO

N45MSSX00 (2007 OG EFTER)



REDUKTIONSGEARKASSE O & S

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF-F (Ford)*Skift alle 1200 timer/ 12 måneder*

HYDRAULISK SYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 32

PRODUKTANBEFALING 2

Perlus AF 32*Skift alle 1200 timer/ 12 måneder*

HYDRAULISK BREMSESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 15

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

KØLESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.